

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 March 2004 (25.03.2004)


PCT

(10) International Publication Number
WO 2004/025840 A1

- (51) International Patent Classification⁷: **H03M 13/45**, 7/30, 7/40, 13/00
- (21) International Application Number: **PCT/IB2003/003870**
- (22) International Filing Date:
4 September 2003 (04.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
02292223.1 11 September 2002 (11.09.2002) EP
- (71) Applicant (for all designated States except US): **KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]**; Groenewoudseweg 1, NL-5621 BA Bindhoven (NL).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **LAMY, Catherine [FR/FR]**; 156 Boulevard Haussmann, F-75008 Paris (FR).
- (74) Agent: **LOUDHEUSDEN-PERSET, Laure**; Société Civile SPID, 156 Boulevard Haussmann, F-75008 Paris (FR).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: METHOD AND DEVICE FOR SOURCE DECODING A VARIABLE-LENGTH SOFT-INPUT CODEWORDS SEQUENCE



(57) Abstract: The invention concerns a method for source decoding a variable-length soft-input codewords sequence ($y[1:T]$) into a soft-output bit sequence ($L_v[1:T]$), the variable-length soft-input input codewords sequence ($y[1:T]$) encoded in accordance with a VLC codewords table. It comprises- a first stage (100) of implementing a stack decoding algorithm for a sequential estimation of an hard-output bit sequence of said variable length soft-input codewords sequence, including storage of intermediate data contained in the stack and generated by the stack decoding algorithm; and- a second subsequent stage (102) of post-processing the stored intermediate data for generating the soft-output bit sequence ($L_v[1:T]$), a soft-output ($L(x[t])$) being provided for each bit.